



JBL PROTEMP S 150

Safety heater-stat with protective basket

Suitable for:



- Heating for an ideal temperature in aquariums with 90 to 200 l content (80 – 100 cm length)
- Easy to install: insert the heater into the protective basket, preselect the temperature on the dial, immerse in the aquarium, attach with suction cups to the internal aquarium pane
- Precise temperature setting: dial covers temperature range 20 - 34 °C, control accuracy +/-0.5°C. Ideal temperature transfer: star-shaped heating element, made of ceramic
- TÜV tested, watertight to a depth of 100 cm, unbreakable safety quartz glass with protective basket. Automatic switch-off in case of sinking water level
- Package contents: safety heater-stat with protective basket, 150 W, 195 cm cable, 2 years guarantee (+2 years upon registration of the product)

You may also be interested in

You can find a complete overview here: <https://www.jbl.de/qr/60424>



JBL Cooler 100
 Cooling fan for fresh- and saltwater aquariums



JBL CoolControl
 Thermostat to regulate cooling fan





JBL PROTEMP S 150

Accessories



JBL PROCLEAN POWER

Cleaner for CO2 diffusers and
aquarium decorations



JBL PROTEMP S 150


Spare parts



JBL ProTemp S Suction Pads



JBL ProTemp S Protect (top)



JBL ProTemp S Protect (middle part, short)



JBL ProTemp S Protect (middle long +suction cup)



JBL ProTemp S Protect (end part)



JBL adapter UK for all flat-pin plugs





JBL PROTEMP S 150



Product information

Heating for aquarium fish

Fish adapt to the ambient temperature. The life functions of cold-blooded animals sink with falling temperatures. The right aquarium temperature is therefore very important to ensure their problem-free food intake and a smooth functioning of their metabolism. Depending on the origin of the fish, the temperature they feel comfortable at varies.

Easy to install


Put the heater into the protective basket included. Preselect the required temperature using the temperature dial and immerse the heater in the water at least to the "min. water level" line. Fasten with the suction cups. A control lamp lights up as soon as the heater is connected to the power supply. The heater can also be mounted horizontally, e.g. for turtle tanks.

Ideal temperature transfer

JBL's safety heater thermostat ensures an ideal temperature transfer in the range between 20 - 34 °C. With the help of the dial a control accuracy of +/- 0.5 °C is ensured. The maximum attainable temperature depends on the water volume and the difference in temperature to the surroundings.

Safety heater thermostat

The protective basket in which the heater is embedded prevents the fish from being scorched. The heater is watertight, can be immersed to a depth of 100 cm and, with its 2 mm strong safety quartz glass, is very stable. If the water level sinks or the heater is removed from the water, a safety protection device in the heater interrupts the electric current and prevents overheating. The heater is TÜV certified.

Further information	
FAQ	✓
Blog	✓
Press	✓
Laboratory/calculator	✗
Worth reading	✓
Spare parts	✓
Video	✓
GarantiePlus	✓
Instructions	✓
QR code	






JBL PROTEMP S 150



Product details

Article data	
Product name	JBL PROTEMP S 150
Art. No.	6042400
EAN number	4014162604248
EAN as barcode	
Length	27,5 cm
For	90-200 l
Expiry months	-
RRP incl. VAT	35,93 €
Base price	-
Nominal filling quantity	-
Base quantity	1
Gross weight	436 g
Net weight	332 g
Weight change	1000

Disposal	
Product name	JBL PROTEMP S 150
Art. No.	6042400
Green dot	✓
Group electronic waste	Small appliances that can be used in private households
Disposal weight	272 g
Battery type	-
Battery return	-
Battery rechargeable	-
Disposal weight battery	-
Non-returnable glass	-
PPK	104 g
Plastic small	-
Plastic large	-
Disposal weight metal	0 g

Features	
Product name	JBL PROTEMP S 150
Art. No.	6042400



Features	
Animal species	Arowana, Artemia, Axolotl, Barbels, Bettas, Bichirs/reedfish, Blowfish, Catfish, Cichlids (South America), Corals, Crayfish, Danions, Discus, Dwarf shrimps, Flowerhorn, Gobies, Goldfish, Gouramis, Guppy, Juvenile fish, Killifish, Livebearers, Loaches, Mussels, Newts, Panchaxes, Rainbowfish, Snails, Spiny eels, Terrapins, Tetra, Tropical butterflyfish, turtle
Animal size	For all animal sizes
Animal age group	All aquarium fish
Volume of habitat	90-200 L (80-100cm)
Material	glass / ceramic / plastic (ABS) / metal
Food type	-
Colour	grey / black
Dosage	-
Transport conditions	-





JBL PROTEMP S 150

Electronic label / illuminant	
Product name	JBL PROTEMP S 150
Art. No.	6042400
Ambient temperature	-
Start time	-
Mercury	-
Tube length	-
Service life	-
Lumen	-
CRI value	-
Dimmable	-
Switching cycles	-
PAR value	-
Energy efficiency class	-
UV-A	-
UV-B	-
UV-C	-
Colour temperature	-
Base designation	-

Technical data	
Product name	JBL PROTEMP S 150
Art. No.	6042400
Range in litres	200 l
Range from - to	90-200l
Range in days	-
Range tank length	80-100
Output in watts	150 W
Output per hour	-
Output per day	-
Height	275 mm
Length	29 mm
Width	29 mm
Diameter	29 mm
Voltage	230 V
For	-
T8 26mm (watt)	-
T5 16mm (watt)	-
Size	-
Content for	-
Filter container volume	-
Volume filter media	-
Hose connections pressure/out	-
Hose connections suction/in	-
Delivery head	-





JBL PROTEMP S 150

Food type	-
Sub product type	-
Dosing	-





Additional information for the specialist trade sector

Article data	
Product name	JBL PROTEMP S 150
Art. No.	6042400
VAT	19%
Sales unit (SU)	1
Volume packaging	1.8l
Dimensions (l/w/h)	50 mm/95 mm/385 mm
Layer	180
Pallet	900
Category of products	3
Customs tariff	85161080
Country of origin	CN
Type of packaging	Faltschachtel/Karton

PU 1 data	
Product name	JBL PROTEMP S 150
Art. No.	6042400
PU 1 material	film gr
PU 1 weight	3.2 g
PU 1 length	95 mm
PU 1 width/depth	100 mm
PU 1 height	385 mm

PU 2 data	
Product name	JBL PROTEMP S 150
Art. No.	6042400
PU 2 material	cardboard gr
PU 2 weight	440 g
PU 2 length	390 mm
PU 2 width/depth	260 mm
PU 2 height	405 mm

Trade data	
Product name	JBL PROTEMP S 150
Art. No.	6042400
Till receipt text	ProTemp S 150W
Shelf placement	-

