Safety heater-stat with protective basket

Suitable for: < 🖈 🐋



- Heating for an ideal temperature in aquariums with 160 to 400 l content (100 120 cm length)
- Easy to install: insert the heater into the protective basket, preselect the temperature on the dial, immerse in the aquarium, attach with suction cups to the internal aquarium pane
- Precise temperature setting: dial covers temperature range 20 34 °C, control accuracy +/-0.5°C. Ideal temperature transfer: star-shaped heating element, made of ceramic
- TÜV tested, watertight to 100 cm, unbreakable quartz safety glass with protection screen. With dryrunning protection against electrical accidents
- Package contents: safety heater-stat with protective basket, 300 W, 195 cm cable, 2 years guarantee (+2 years upon registration of the product)



You may also be interested in

You can find a complete overview here: https://www.jbl.de/gr/60426





JBL Cooler 100 Cooling fan for fresh- and saltwater aquariums



JBL CoolControl Thermostat to regulate cooling fan





## JBL PROTEMP S 300







JBL PROCLEAN POWER Cleaner for CO2 diffusers and aquarium decorations

















JBL ProTemp S Suction Pads

JBL ProTemp S Protect (top)

JBL ProTemp S Protect (middle part, short)

JBL ProTemp S Protect (middle long +suction cup)





JBL ProTemp S Protect (end part)

JBL adapter UK for all flat-pin plugs





Product information

Heating for aquarium fish Fish adapt to the ambient temperature. The life functions of cold-blooded animals sink with falling temperatures. The right aquarium temperature is therefore very important to ensure their problem-free food intake and a smooth functioning of their metabolism. Depending on the origin of the fish, the temperature they feel comfortable at varies.

### Easy to install

Put the heater into the protective basket included. Preselect the required temperature using the temperature dial and immerse the heater in the water at least to the "min. water level" line. Fasten with the suction cups. A control lamp lights up as soon as the heater is connected to the power supply. The heater can also be mounted horizontally, e.g. for turtle tanks.

### Ideal temperature transfer

JBL's safety heater thermostat ensures an ideal temperature transfer in the range between 20 - 34 °C. With the help of the dial a control accuracy of +/- 0.5 °C is ensured. The maximum attainable temperature depends on the water volume and the difference in temperature to the surroundings.

### Safety heater thermostat

The protective basket in which the heater is embedded prevents the fish from being scorched. The heater is watertight, can be immersed to a depth of 100 cm and, with its 2 mm strong safety quartz glass, is very stable. If the water level sinks or the heater is removed from the water, a safety protection device in the heater interrupts the electric current and prevents overheating. The heater is TÜV certified.

Further information	
FAQ	~
Blog	~
Press	✓
Laboratory/calculator	×
Worth reading	<ul> <li>✓</li> </ul>
Spare parts	✓
Video	✓
GarantiePlus	✓
Instructions	~
QR code	



### Article data JBL PROTEMP S 300 Product name Art. No. 6042600 EAN number 4014162604262 EAN as barcode 37,5 cm Length For 160-400 I Expiry months RRP incl. VAT 37,56€ Base price Nominal filling quantity Base quantity 1 Gross weight 530 g Net weight 402 g 1000 Weight change

Disposal	
Product name	JBL PROTEMP S 300
Art. No.	6042600
Green dot	✓
Group electronic waste	Small appliances that can be used in private households
Disposal weight	332 g
Battery type	-
Battery return	-
Battery rechargeable	-
Disposal weight battery	-
Non-returnable glass	-
РРК	128 g
Plastic small	-
Plastic large	-
Disposal weight metal	0 g

Features	
Product name	JBL PROTEMP S 300
Art. No.	6042600



Date: 31.12.2023 Produced by:

### TECHNICAL PRODUCTS TECHNIK TECHNIQUE





Features	
Animal species	Arowana, Artemia, Axolotl, Barbels, Bettas, Bichirs/reedfish, Blowfish, Catfish, Cichlids (South America), Corals, Crayfish, Danions, Discus, Dwarf shrimps, Flowerhorn, Gobies, Goldfish, Gouramis, Guppy, Juvenile fish, Killifish, Livebearers, Loaches, Mussels, Newts, Panchaxes, Rainbowfish, Snails, Spiny eels, Terrapins, Tetra, Tropical terrapins, Veitiails, freshwater butterflyfish, turtle
Animal size	For all animal sizes
Animal age group	All aquarium fish
Volume of habitat	160-400 L (100-120cm)
Material	glass / ceramic / plastic (ABS) / metal
Food type	-
Colour	grey / black
Dosage	-
Transport conditions	-





Electronic label / illuminant	
Product name	JBL PROTEMP S 300
Art. No.	6042600
Ambient temperature	-
Start time	-
Mercury	-
Tube length	-
Service life	-
Lumen	-
CRI value	-
Dimmable	-
Switching cycles	-
PAR value	-
Energy efficiency class	-
UV-A	-
UV-B	-
UV-C	-
Colour temperature	-
Base designation	-

Technical data	
Product name	JBL PROTEMP S 300
Art. No.	6042600
Range in litres	400
Range from - to	160-4001
Range in days	-
Range tank length	100-120
Output in watts	300 W
Output per hour	-
Output per day	-
Height	375 mm
Length	29 mm
Width	29 mm
Diameter	29 mm
Voltage	230 V
For	-
T8 26mm (watt)	-
T5 16mm (watt)	-
Size	-
Content for	-
Filter container volume	-
Volume filter media	-
Hose connections pressure/out	-
Hose connections suction/in	-
Delivery head	-







Food type	
Sub product type	•
Dosing	-





## Additional information for the specialist trade sector

Article data	
Product name	JBL PROTEMP S 300
Art. No.	6042600
VAT	19%
Sales unit (SU)	1
Volume packaging	2.251
Dimensions (l/w/h)	50 mm/95 mm/475 mm
Layer	120
Pallet	600
Category of products	3
Customs tariff	85161080
Country of origin	CN
Type of packaging	Faltschachtel/Karton

PU 1 data	
Product name	JBL PROTEMP S 300
Art. No.	6042600
PU 1 material	film gr
PU 1 weight	3.6 g
PU 1 lengh	95 mm
PU 1 width/depth	100 mm
PU 1 height	475 mm

PU 2 data	
Product name	JBL PROTEMP S 300
Art. No.	6042600
PU 2 material	None
PU 2 weight	-
PU 2 lengh	-
PU 2 width/depth	-
PU 2 height	-

Trade data	
Product name	JBL PROTEMP S 300
Art. No.	6042600
Till receipt text	ProTemp S 300W
Shelf placement	-

